

Public Works Department

515 Clark Avenue, Ames, Iowa 50010 Phone 515-239-5160 ♦ Fax 515-239-5404

37

June 7, 2016

Honorable Mayor and Council Members City of Ames Ames, Iowa 50010

c foi

Ladies and Gentlemen:

I hereby certify that the public utility improvements, curb & gutter, and asphalt base paving construction required as a condition for approval of the final plat of **South Fork, 8th Addition** have been completed in an acceptable manner by **Ames Trenching and Excavating and Manatts, Inc. of Ames, IA**. The above-mentioned improvements have been inspected by the Engineering Division of the Public Works Department of the City of Ames, Iowa and found to meet City specifications and standards.

As a result of this certification, it is recommended that the financial security for public improvements on file with the City for this subdivision be set at \$23,450.00. The remaining work covered by this financial security includes asphalt surface paving, and final utility fixture adjustments.

Sincerely,

John C. Joiner, P.E.

Director

JJ/jc

cc: Finance, Contractor, Construction Supervisor, PW Senior Clerk, Planning & Housing, Subdivision file

Description	Unit	Quantity
MOBILIZATION	LS	1
EXCAVATION, CLASS 13	CY	1,500
SUBGRADE PREPARATION, 12-INCH	SY	2,310
SANITARY SEWER GRAVITY MAIN, TRENCHED,8-INCH, PVC	LF	618
SANITARY SEWER SERVICE STUB, 4-INCH, PVC	EA	17
SANITARY SEWER CLEANOUT	EA	1
STORM SEWER, TRENCHED, RCP CLASS III, 15-INCH	LF	327
FOOTING DRAIN COLLECTOR, 6-INCH	LF	388
FOOTING DRAIN CLEANOUT, 6-INCH	EA	1
FOOTING DRAIN OUTLET AND CONNECTION, 6-INCH	EA	1
STORM SEWER SERVICE STUB, 1.5-INCH, PVC	EA	17
WATER MAIN, TRENCHED, PVC SDR18, 8-INCH	LF	691
WATER SERVICE STUB, CURB STOP & BOX, 1-INCH	EA	17
FITTINGS, 8-INCH, 45 DEGREE ANGLE	EA	2
FITTINGS, 8-INCH, SLEEVE	EA	1
VALVE, MJ GATE, 8-INCH	EA	1
FIRE HYDRANT ASSEMBLY	EA	4
RELOCATE FLUSHING DEVICE (BLOWOFF), 8-INCH	EA	1
INTAKE, SW-301	EA	2
INTAKE, SW-501	EA	1
INTAKE, SW-503	EA	1
CURB & GUTTER, 30-INCH	LF	1,371
PAVEMENT, HMA, 8-INCH	SY	1,601
PCC SIDEWALK, 6-INCH	SY	26
DETECTABLE WARNING	SF	66
SEEDING, TYPE 1 LAWN MIX	ACRE	1
SILT FENCE, INSTALL, MAINTAIN & REMOVE	LF	950
INLET PROTECTION DEVICE, INSTALL, MAINTAIN & REMOVE	EA	6
STABILIZED CONSTRUCTION ENTRANCE	EA	2